



### **VHF MARINE TRANSCEIVERS**

# **Top Performance Ultra Compact VHF**



**BUILT-IN** 

**GPS RECEIVER** 

Ultra Compact Body (W  $\times$  H  $\times$  D; 156.5  $\times$  66.5  $\times$  110.1 mm; 6.2  $\times$  2.6  $\times$  4.3 in) Easy Installation in Limited Space

New Speaker Delivers Dynamic, Clear Audio

Built-in Class D DSC with a CH70 Dedicated Receiver (IC-M330G meets ITU-R M.493-14)

Class Leading Receiver Performance (IMD and Selectivity: more than 70 dB)

Intuitive Operation with Icom Marine User Interface

GPS Receiver Built-in with Supplied GPS Antenna (IC-M330G)

Easy-to-Read Full Dot-Matrix Display

IPX7 Submersible Construction (1 m depth of water for 30 minutes)

- AquaQuake<sup>™</sup> Draining Function
- Made in Japan Quality and Reliability



#### VHF MARINE TRANSCEIVERS

#### **Ultra Compact Body, Flexible Installation**

The IC-M330/G has a palm-sized compact body (W×H×D: 156.5 ×  $66.5 \times 110.1$  mm;  $6.2 \times 2.6 \times 4.3$  in). The radio can be installed in limited space.

#### New Speaker Delivers Dynamic, Clear Audio

A new speaker design delivers dynamic and clear sound over a wide bass and treble range. The IC-M330/G provides a distortion-free clear audio even at full volume.

#### **Built-in Class D DSC**

The radio monitors CH 70 continuously, even while you are receiving another channel. DSC functions include: distress, individual, group, all ships, urgency, safety, position request/report, polling request and DSC test calls.

#### **Class Leading Receiver Performance**

The radio provides reliable communication in RF busy environment like a marina. (Selectivity and IMD: more than 70 dB)

#### Intuitive Operation with Icom Marine User Interface

A combination of the directional keypad and soft keys provides simple, smooth operation. Most used functions are assigned to soft keys for quick one push function access.


#### **OPTIONS**

CLASS B AIS TRANSPONDER MA-500TR



#### SPECIFICATIONS

GENERAL		
Frequency range Tx		156.025–161.600 MHz
	470	156.050–163.275 MHz 156.525 MHz
Usable channels		USA, CAN, INT, WX channels
Type of emission		16K0G3E (FM), 16K0G2B (DSC)
- 21		
Power supply requirement		13.8 V DC nominal (11.7–15.9 V DC)
Current drain (at 13.8 V DC)		
Tx 25 W output		5 A
Rx AF max.		1 A
Operating temperature range		-20°C to +60°C; -4°F to +140°F
Antenna impedance		50 Ω (SO-239)
Dimensions (W×H×D)		156.5 × 66.5 × 110.1 mm;
(projections not included)		6.2 × 2.6 × 4.3 in
Weight (approx.)		730 g; 1.6 lb
NMEA formats	In	RMC, GGA, GNS, GLL, VTG
	Out	DSC, DSE, RMC, GSA, GSV
TRANSMITTER		
Output power (at 13.8 V DC)		25 W, 1 W
Max. frequency deviation		±5 kHz
Frequency tolerance		±5 ppm
Spurious emissions		Less than -70 dBc (High)
		Less than -56 dBc (Low)



HM-235B/W

HAND MICBOPHONE

Same as supplied.

Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

#### Applicable IP Rating

**Ingress Protection Standard** IPX7 (Waterproof protection) Water

Supplied accessories: \* Only for the IC-M330G. HM-235B/W hand microphone DC power cable Mounting bracket kit • GPS antenna (5 m; 16.4 ft cable)\*

## IC-M330G·IC-M330

#### **GPS Receiver Built-in (IC-M330G)**

A built-in GPS receiver provides your location, bearing and speed by using information from GPS. GLONASS and SBAS. The acquired position information can be used for DSC calls.




#### Made in Japan Quality and Reliability


All Icom products are tested to pass rigorous in-house tests as well as environmental tests at the Wakayama Icom plant before shipping. Our world-leading products and guality is tradition.

#### And More

- IPX7 submersible (1 m depth of water for 30 minutes)
- AguaQuake<sup>™</sup> prevents audio degradation from a water-logged speaker
- Common NMEA interface for external GPS/NAV connection
- MA-500TR Class B AIS transponder compatible
- Tag scan and favorite channel functions
- Dual/tri-watch function for monitoring CH16 and/or call channel
- Priority scan function Display and keypad backlighting
- External speaker connection Weather channel with weather alert
- Supplied hand microphone, HM-235B/W, with channel up/down keys and a CH16/Call channel key
- · 3-digit or 4-digit channel display selectable



#### DIMENSIONS



Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan). All other trademarks are the properties of their respective holders.

ICOM Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world

Icom America Inc. 12421 Willows Road NE. Kirkland, WA 98034, U.S.A Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com UBL: http://www.icomamerica.com

#### Icom Canada

Glenwood Centre #150-6165 Glenwood Centre #150-6165 Highway 17A, Delta, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-4090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

#### Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

#### Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 Au der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0 Fax: +49 (6196) 76685-50 E-mail: Info@icomeurope.com URL: http://www.icomeurope.com

#### Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 E-mail: icom@icomspain.com URL: http://www.icomspain.com

#### Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

#### Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 
 1505 Toulouse Cedex 5, France

 Phone: +33 (5) 61 36 03 03

 Fax: +33 (5) 61 36 03 00


 F-mail: icom@icom-france.com

 URL: http://www.icom-france.com

#### Icom (Australia) Pty. Ltd. Unit 1 / 103 Garden Boad Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505

E-mail: sales@icom.net.au URL: http://www.icom.net.au Your local distributor/dealer:

Count on us!



FLUSH MOUNT KIT

MBF-5

American Communication Systems Discover the Power of Communications™ http://www.ameradio.com